

BUBBLE 600 STABLE WHITE

(STANDARD GRADE)

FULL EFFECT







PROJECT

SPEC TYPE

NOTES

216.5" 216.5" 7.48" -Ø23.62"-











GENERAL INFORMATION:

The BUBBLE 600 STABLE WHITE seamlessly integrates lighting effects with its design, exhibiting a shape that adapts independently to the light beam direction and effortlessly blends into any setting, providing ample room for architectural creativity.

The BUBBLE 600 STABLE WHITE has a size of 23 inches and two color temperatures to chose from: 3000K and 4000K with full effect lighting.

OPTICS:

Smooth opal polycarbonate diffuser, injection-molded, shock-resistant, and anti-aging.

FINISHING:

Matt White

BODY:

Round metal frame, seats for the electrical components and anchor points for the suspension device and diffusers.

VOLTAGE:

110-277V



LIGHTING:

LED



LIGHTING EFFICIENCY:

≥ 60 lm/w

IP RATING:

20



APPLIANCE CLASS:

L



WWW.BULLARDCOLLECTION.COM





Contact Us:

sales@gordonbullard.com www.cerchiolighting.com 1 877-964-4646



PROJECT

SPEC TYPE

NOTES















CODE

C-15SL1

-FE

-S

- D24

- 7-5

- 55W

-80

-AE

Example: C-15SL1-FE-S-D24-7-5-55W-80-30K-DL-AE-CS-RE

1 LIGHT DISTRIBUTION:

-FE Full Effect

X

2 INSTALLATION TYPE:

-S Suspended

3 CIRCLE DIAMETER:

-**D24** 24"

4 SIDE PROFILE HEIGHT:

-7-5 7.5"

5 POWER:

-55W 55 Watts

6 LED CRI:

-80 CRI 80

7 SPECIFY CCT AND LIGHT EMISSION:

-30K 3000K / 2510 lm

-40K 4000K / 2700 lm

8 DIMMING OPTION:

-STD Non-Dimmable

-DL DALI

9 FIXTURE FINISH:

-AE Matt White

WWW.BULLARDCOLLECTION.COM





Contact Us:



PROJECT

SPEC TYPE

NOTES

HOW TO ORDER:

CODE

Example: C-15SL1-FE-S-D24-7-5-55W-80-30K-DL-AE-CS-RE

C-15SL1

10 CANOPY OPTIONS:





-CS cable straight

nexus central

11 ADDITIONAL FEATURES:

-RE Remote Emergency-OS Occupancy Sensor

-DS Daylight Sensor / Light Harvesting

* E.G. : RE = Remote Emergency













