

FRUIT 2 CHANDELIER (STANDARD GRADE)

BEAM UP & DOWN



PROJECT

SPEC TYPE

NOTES

GENERAL INFORMATION:

FRUIT 2 CHANDELIER - STANDARD GRADE offers a unparalleled value cost proposition in 7 standard sizes ranging from 23.6 to 196.9 inch diameters. Direct and indirect lighting from 2700K to 4000K . Offering two standard canopy and mounting options. Housing is full aluminum construction with both standard powder coating in black or white as well as custom RAL options. Complete Collection offers optional Emergency Back up kits, Motion, Occupancy, and Light harvesting control interfaces.

OPTICS:

PMMA lenses, Anti-UV Operation

FINISHING:

Matt White, Matt Black, custom on request

BODY:

Aluminum body construction

VOLTAGE:

110-277V



LIGHTING:

LED



LIGHTING EFFICIENCY:

≥ 85lm/w

IP RATING:

44



APPLIANCE CLASS:

I



WWW.BULLARDCOLLECTION.COM

OUTDOOR
TECHNICAL
DECORATIVE



WE WELCOME ALL CUSTOM ORDERS

Contact Us:

sales@gordonbullard.com
www.cerchiolighting.com
1 877-964-4646

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

©Bullard & Company 2024 All Rights Reserved

Updated 01/10/2024

PROJECT

SPEC TYPE

NOTES

HOW TO ORDER:

CODE

Example:

NS-LL0115-DI-S-D24-2-7-65W-80-27K-DIM-SW-CS

NS-LL0115

1 LIGHT DISTRIBUTION:

-DI

-DI DIRECT/INDIRECT



2 INSTALLATION TYPE:

-S

-S Suspended

3 CIRCLE DIAMETER:

-D24 24" -D79 79"
-D36 36" -D119 119"
-D48 48" -D197 197"
-D60 60"

4 SIDE PROFILE HEIGHT:

-2-7

-2-7 2.7"

5 POWER AND LIGHT EMISSION:

CODE = TOTAL WATTS | Ø

DIRECT LUMENS | WATTS

INDIRECT LUMENS | WATTS

-65W	23.6"	3,400 lm/40W	2,125 lm/25W
-80W	35.4"	4,760 lm/56W	2,040 lm/24W
-120W	47.2"	7,140 lm/84W	3,060 lm/36W
-135W	59.1"	7,650 lm/90W	3,825 lm/45W
-150W	78.8"	8,925 lm/105W	3,825 lm/45W
-300W	118.1"	17,850 lm/210W	7,650 lm/90W
-480W	196.9"	28,560 lm/336W	12,240 lm/144W

*E.G : 65W = 65 total Watts

6 LED CRI:

-80 CRI 80

-90 CRI 90

7 SPECIFY CCT:

-27K 2700K -35K 3500K
-30K 3000K -40K 4000K



LED



IP44



WWW.BULLARDCOLLECTION.COM

OUTDOOR

TECHNICAL

DECORATIVE



WE WELCOME ALL CUSTOM ORDERS

Contact Us:

sales@gordonbullard.com

www.cerchiolighting.com

1 877-964-4646

PROJECT
SPEC TYPE
NOTES



HOW TO ORDER:

CODE

8 DIMMING OPTION:

- STD Non-Dimmable
- DIM 1-10V

9 FIXTURE FINISH:


- SW Matt White
- SB Matt Black
- RAL Custom RAL on request*

* E.G. : RAL = #3020

10 CANOPY OPTIONS:



CS
cable
straight



CSS
central
standard

11 ADDITIONAL FEATURES:


- RE Remote Emergency
- OS Occupancy Sensor
- DS Daylight Sensor/Light Harvesting

* E.G. : RE = Remote Emergency


12

CHANDELIER CONFIGURATIONS:


FRUIT circles may be ordered as separate circle pendants and/or in cluster configurations of two, three or five fixtures of various sizes, as well as custom clusters. (Consult factory for custom designs.)




C01.




C02.




C03.



C04.



C05.



C06.



C07.



C08.



C09.



C10.



C11.



C12.